

HYDRAULIC DRIVEN HEADS



ROAD PLANERS FOR SKID STEERS	Engine (hp)	Flow Requirements (gal/min)	Pressure (PSI)	Working width (in)	Total width (in)	Weight (lbs)	Working depth (in)
RPL/SSL	60-135	26-53	2600-5080	18-59	65	1990-3329	0-7
RPM/SSL	75-135	32-45	2600-5080	24	65	2580	0-10
WHEEL SAWS FOR SKID STEERS	Engine (hp)	Flow Requirements (gal/min)	Pressure (PSI)	Working width (in)	Total width (in)	Weight (lbs)	Working depth (in)
RWL/SSL	50-75	21-33	2600-5080	1-2	65	1962	10-14
RWM/SSL	75-135	32-45	2900-5080	3.2-4.7	65	2900-3010	10-20
STONE CRUSHERS FOR SKID STEERS	Engine (hp)	Flow Requirements (gal/min)	Pressure (PSI)	Working width (in)	Total width (in)	Weight (lbs)	Working depth (in)
STC/SSL	90-120	29-40	3200-5080	63	75	2668	6
ROAD PLANERS FOR EXCAVATORS	Excavator weight (t)	Flow Requirements (gal/min)	Pressure (PSI)	Working width (in)	Total width (in)	Weight (lbs)	Working depth (in)
RPL/HY	5-8	13-24	2600-5080	12	24	882	0-4.5
RPL/EX	8-14	28-42	2600-5080	18	31	1543	0-5.3

The data refers to the minimum and maximum values of the product ranges. Refer to the technical table of the specific model for more details.

DP063007 USA - 03/2026 - by FAE S.p.A.

CONSTRUCTION Hydraulic Driven Heads



HYDRAULIC DRIVEN HEADS

FAE's hydraulic driven heads from the Construction line are designed for shredding asphalt and concrete, or crushing stones. The line offers solutions for skid steer loaders and excavators.

ROAD PLANERS FOR SKID STEERS

 60-135 hp  10 in max

For milling asphalt and concrete road surfaces.



WHEEL SAWS FOR SKID STEERS

 50-135 hp  20 in max

Utility trenchers for laying electrical, water, gas, and fiber optic conduits.



STONE CRUSHERS FOR SKID STEERS


 90-120 hp  6 in max

For crushing stones, asphalt and concrete, even deep underground.



ROAD PLANERS FOR EXCAVATORS

 5-14 t  5.3 in max

 13-42 gal/min

For milling asphalt and concrete road surfaces.



LEARN MORE ABOUT
THE HYDRAULIC DRIVEN
HEADS FROM THE
CONSTRUCTION LINE

