

# PTO DRIVEN HEADS

<b>SOIL STABILIZERS FOR TRACTORS</b>	<b>Tractor (hp)</b>	<b>PTO (rpm)</b>	<b>Working width (in)</b>	<b>Total width (in)</b>	<b>Weight (lbs)</b>	<b>Working depth (in)</b>
STABI/FRS	300-500	1000	91-101	108-118	13889-14881	20
STABI/H	300-500	1000	90-100	105-114	16094-16535	6-22
<b>MULTITASKS FOR TRACTORS</b>	<b>Tractor (hp)</b>	<b>PTO (rpm)</b>	<b>Working width (in)</b>	<b>Total width (in)</b>	<b>Weight (lbs)</b>	<b>Working depth (in)</b>
MTL	140-300	1000	58-96	72-109	7430-9634	6-11 (G/3) 6-11 (R)
MTM	220-360	1000	81-90	98-108	13117.5-14330	9-16 (G/3) 10-16 (R)
MTH	300-500	1000	91-101	114-124	17417-18353	13-20 (G/3) 13-20 (R)

The data refers to the minimum and maximum values of the product ranges. Refer to the technical table of the specific model for more details.

DP062007 USA - 04/2026 - by FAE Group S.p.A.



## CONSTRUCTION PTO Driven Heads



# PTO DRIVEN HEADS

FAE's PTO driven heads in the Construction line are designed for mixing, stabilizing, crushing and shredding. The line offers solutions for low, medium, high and extremely high horsepower tractors. The product line includes soil stabilizers and multitask heads that can be used for a wide variety of tasks.

## SOIL STABILIZERS

 300-500 hp  22 in max

For soil mixing and stabilization, also with special binders.



## MULTITASKS

 140-500 hp  20 in max

Stone crushing, mixing, stabilizing, shredding - all in one multitask head.



LEARN MORE ABOUT  
THE PTO DRIVEN  
HEADS FROM THE  
CONSTRUCTION LINE

