

REMOTE CONTROLLED TRACKED CARRIERS

TECHNICAL DATA	RCU45	RCU55	RCU75	RCU120
Engine Gross Power (hp)	44	56	74	120
Engine Emission	Tier 4 Final - EU Stage V	Tier 4 Final	Tier 4 Final	Tier 4 Final - EU Stage V
Closed Loop Max Flow (gpm) - Max Pressure (psi)	16 - 4205	20 - 4210	27.7 - 4650	40 - 5148
Open Loop Max Flow (gpm) - Max Pressure (psi)	AUX 1: 5.3 - 2175	AUX 1: 4.5 - 3045	AUX 1: 4 - 3045	AUX 1: 4 - 3045
	AUX 2: 7.9 - 2175	AUX 2: 4.5 - 3045	AUX 2: 4 - 3045	AUX 2: 4 - 3045
	-	AUX 3: 7 - 3045	AUX 3: 10.5 - 3045	AUX 3: 10.5 - 3045
Hydraulic Oil Tank Capacity (gal)	6.6	11	12	15
Fuel Tank Capacity (gal)	8.2	11	17	20
DEF AdBlue® Tank (gal)	-	-	-	4
Rubber Track Pitch (mm) - Width (in)	72 - 10, High profile	72 - 10, High profile	86 - 13, High profile	86 - 13, High profile
Lower Rollers (HD style)	4 + 4, Double flange	5 + 5, Double flange	6 + 6, Double flange	6 + 6, Double flange
Front Idler / Tensioning Group	Single flange - Automatic tensioning system	Double flange - Automatic tensioning system	Double flange - Automatic tensioning system	Double flange - Automatic tensioning system
Voltage (V)	12	12	12	12
Max Forward Speed (mph)	3 (L mode); 4.6 (H mode)	5	4.7	3.1
Max Reverse Speed (mph)	3 (L mode); 4.6 (H mode)	5	4.7	3.1
Gradeability	55°, All directions	55°, All directions	55°, All directions	55°, All directions
Operating Weight (lbs)	2910 (std equipment / std rubber tracks)	4894 (std equipment / std rubber tracks)	7452 (std equipment / std rubber tracks)	8488 (std equipment / std rubber tracks)
Ground Pressure (psi)	3.7 (std equipment / std rubber tracks / BL0/RCU45-125)	4.7 (std equipment / std rubber tracks / BL1/RCU55-125)	5 (std equipment / std rubber tracks / BL2/RCU75-150)	5.8 (std equipment / std rubber tracks / UML/RCU120-150)

The data refers to the minimum and maximum values of the product ranges. Refer to the technical table of the specific model for more details.

AVAILABLE ATTACHMENTS

RCU45	Head type	Working width (in)	Total width (in)	Weight (lbs)	Max shredding Ø (in)	Max working depth (in)
BL0/RCU45-125	Forestry mulcher	49	57	882	4	-
PML/RCU45-130	Flail mulcher	52	57	661	2	-

RCU55	Head type	Working width (in)	Total width (in)	Weight (lbs)	Max shredding Ø (in)	Max working depth (in)
BL1/RCU55-125	Forestry mulcher	49	59	1058	5	-
PML/RCU55-150	Flail mulcher	59	68	1179	2	-
SCL/RCU55	Stump cutter	33	44	928	14	18

RCU75	Head type	Working width (in)	Total width (in)	Weight (lbs)	Max shredding Ø (in)	Max working depth (in)
BL2/RCU75-150	Forestry mulcher	58	70	1852	6	-
PMM/RCU75-75	Flail mulcher	70	77	1587	3.1	-
SCL/RCU75	Stump cutter	37	44	926	16	20

AVAILABLE ON REQUEST Road planer RPL/SSL and wheel saw RWL/SSL

THIRD-PARTY ATTACHMENTS WITH THE SAE CONNECTION FOR SKID STEERS.

RCU120	Head type	Working width (in)	Total width (in)	Weight (lbs)	Max shredding Ø (in)	Max working depth (in)
UML/SONIC/RCU120-150	Forestry mulcher	62	74	2668	8	-
BL4/SONIC/RCU120-150	Forestry mulcher	62	74	2745	12	-
PMM/SSL-175	Flail mulcher	70	79	1874	3	-
SCL/SSL	Stump cutter	37	46	992	16	20

AVAILABLE ON REQUEST Road planer RPL/SSL, road planer RPM/SSL, wheel saw RWM/SSL and stone crusher STC/SSL

THIRD-PARTY ATTACHMENTS WITH THE SAE CONNECTION FOR SKID STEERS.

DP065007 USA - 04/2026 - by FAE S.p.A.



LAND CLEARING Remote controlled tracked carriers



fae-group.com

USA

REMOTE CONTROLLED TRACKED CARRIERS

Compact, remote-controlled tracked carriers which can be equipped with FAE attachments for vegetation management, forestry work, or roadwork or with compatible third-party attachments.



RCU45

RCU55

RCU75

RCU120

MODEL	0 hp	50 hp	100 hp	150 hp
RCU45		44 hp		
RCU55			56 hp	
RCU75				74 hp
RCU120				120 hp

RCU45



44 hp



Compatible with FAE App

AVAILABLE ATTACHMENTS

BL0/RCU - Forestry mulcher
PML/RCU - Flail mulcher



RCU55



56 hp



Compatible with FAE App

AVAILABLE ATTACHMENTS

BL1/RCU - Forestry mulcher
PML/RCU - Flail mulcher
SCL/RCU - Stump cutter



RCU75



74 hp



Compatible with FAE App

AVAILABLE ATTACHMENTS

BL2/RCU - Forestry mulcher
PMM/RCU - Flail mulcher
SCL/RCU - Stump cutter
RPL/SSL - Road planer
RWL/SSL - Wheel saw

Third-party attachments with the SAE connection for skid steers



RCU120



120 hp



Compatible with FAE App

AVAILABLE ATTACHMENTS

UML/RCU - Forestry mulcher
BL4/RCU - Forestry mulcher
PMM/RCU - Flail mulcher
SCL/RCU - Stump cutter
RPL/SSL - Road planer
RPM/SSL - Road planer
RWM/SSL - Wheel saw
STC/SSL - Stone crusher

Third-party attachments with the SAE connection for skid steers



LEARN MORE ABOUT THE LAND CLEARING RCU RANGE

